



Mr. Crystal

Crystal Water
Leisured Wellness



Aquark Technology Limited

Web: www.aquark.com

Tel: +86 20 3781 4693

Mail: sales@aquark.com

Address: Keyuan Two Road, Gaoli Development Zone, Ronggui Shunde District, Foshan, P.R.China 528306



FULL-TOUCH SCREEN

Ease with Fingertips



3-Mode Functionality

Smoothly Alternate between 100% Boost, Scheduled Auto and Manual Modes



Cell Auto-Protection

Automatic Current Adjustment for Slowing Wear and Tear



External Device Control

Harmonize with Key Pool Device

100 LEVELS OF CONTROL





MORE FEATURES



IP65 Protection



App Control



Salinity Detection



Replaceable Electrode



Self-cleaning Cell



Optional Dosing Pump

PARAMETERS OF MR. CRYSTAL

Model	MCS08	MCS16	MCS26	MCS36
Production (g/h, 3000 PPM)	8	16	26	36
Salt Level (Recommended)	3 ~ 5 (recommended 3g/L)			
Advised Pool Volume (m³)*	25-40	40-70	70-100	100-135
	TECHNICAL SPECIFICATIONS			
Advised Water Flux (m³/h)	5 ~ 18			
Power Supply	100-240V~ 50/60Hz			
Max Power Consumption (W)	62	104	151	197
Operating Temperature (°C)	-5 ~ 42			
Salinity Test	Salt Level Detection (accuracy ±500PPM)			
Self-cleaning	Default 4h (Range: 1 ~ 10h)			
Dosing Pump	External (Optional)			
Communications	MODBUS RS485 / Wi-Fi / Dry Contact			
Control Unit Dimension LxWxH (mm)	245 x 200 x 75			
	ELECTROLYSIS CELL			
Water Connection (mm)	63 / 60.3 / 50 / 48.3			
Water Temperature (°C)	10 ~ 40			
Maximum Pressure (Bar)	4.5			
Cell Life (h)	8,000			
	PACKAGING SPECIFICATIONS			
Gross Weight (kg)	7			
Packaging Dimension LxWxH (mm)	403 x 353 x 300			
Qty per 20'FT/140'HQ (sets)	561 / 1338			

* Water temperature no more than 28°C; In hot climates, reduce the volume by 25-40%.